


HAULMASTER 600-30P is a robust, safe, fast, and reliable personnel vehicle designed for the rapid movement of mine personnel and materials in demanding underground applications.



The robust and reliable four-wheel drive, articulated Haulmaster 600-30P consists of a power-shift transmission powered by a choice of diesel engines connected to heavy-duty Dana axles. The rugged frame and articulated carrier make the Haulmaster 600-30P a very durable and extremely maneuverable unit even in the tightest situations. The rear personnel area can be designed to meet customer's specific requirements or personnel carrying capacity. In underground mining and tunneling operations, the Haulmaster 600-30P will ensure workers reach the work site in a safe, comfortable, and timely manner.

FEATURES:

- Comfortable and safe personnel compartment
- Up to 30 person carrying capacity in personnel compartment
- Wide folding access stairs for personnel safety
- Dual controls (interior and exterior) to raise lower access stairs
- Various seating arrangements and capacities to suit customer requirements
- Individual seating options available including mechanical and air ride seating
- Fully enclosed, climate controlled personnel compartment option available

SPECIFICATIONS:

PERSONNEL COMPARTMENT

Fixed bench seating capacity	30
Dual electronic controls for access stairs	
Dimensions	2337 mm width x 4329 mm length 7'- 8" width x 14'- 2" length

MISCELLANEOUS

- Central grease point – manual
- Standard gauges and instrumentation
- ANSUL fire suppression system - manual
- Copy of Parts/Operator/Service manuals
- Passenger seating
- Suspension seating (operator/passenger)
- ROPS/FOPS certified canopy – operator compartment
- ROPS/FOPS certified canopy – personnel compartment

ENGINE

Cat® C6.6 ACERT, inline 6, 4 stroke cycle, diesel	
U.S. EPA Tier 3, EU Stage III A	
Power rating @ 2200 rpm	158 kW / 212 hp
Compression Ratio	16.5:1
Displacement	6.6 L (402.8 in³)
Exhaust: catalytic purifier with silencer	
Fuel tank volume	238 L

TRANSMISSION

- Dana powershift, 32000 series
- 4 speeds forward and reverse
- 4 wheel drive

AXLES

Dana 113, planetary type	
Oscillation (rear axle)	± 7°

BRAKES

- Service: wet disc (integrated), internal SAHR
- Emergency & parking: SAHR

TIRES

- Mine type, 10.00 – 20

STEERING

Hydraulic, articulated	
Steering angle	± 38°

HYDRAULICS

Steering	
170 bar, 190 L/min/2200 rpm	
Hydraulic oil tank volume	230 L


ELECTRICAL SYSTEM

24 V	
Battery	2 x 12 VDC
Tramming/working LED lights	4 front / 4 rear
Brake lights	2 rear
Horn & reverse alarm	

OPTIONAL EQUIPMENT

- | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> Various engine makes/models Various seating arrangements/capacities Automatic centralized lubrication system 24 V hydraulic oil transfer pump Fast fill system Cold weather package Strobe light Swivel seat Exhaust system wrap Solid or foam filled tires Power pack | <ul style="list-style-type: none"> ROPS/FOPS approved enclosed cabin Foldable bench seating Individual seating (mechanical, air ride) Wheel chocks Driver door interlock ANSUL Checkfire fire suppression system Camera system Air ride seating (operator/passenger) Midship or front seated operator cabin Remote brake release for towing Other options available upon request |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

PERSONNEL CARRIER ARRANGEMENT



BENCH SEATING




INDIVIDUAL SEATING

PERSONNEL CARRIER CAPACITIES

<i>Type of seating</i>	<i>Personnel Capacity</i>
Fixed bench seating (standard)	30 (+1 operator, +1 passenger)
Folding bench seating (optional)	30 (+1 operator, +1 passenger)
Individual seating (optional)	27 (+1 operator, +1 passenger)
*Various seating arrangements/capacities available	

MEASUREMENTS



DIMENSIONS	mm	inches	CONT'D	mm	inches
Width	2362	93	Inside turning radius	5695	224
Height	2391	94	Outside turning radius	8533	336
Ground clearance	344	13			
Length	8985	353			
WEIGHT	kg	lbs			
Total	14990	33047			

All weights, dimensions, and other data reflect a standard unit unless otherwise stated. RDH reserves the right to change specifications and equipment without notice. Consult RDH Mining Equipment sales representative for specific information.